

ROSEMOUNT 8750W MAGNETIC FLOWMETER



Rosemount reliability for utility, water and wastewater applications

RELIABLE UTILITY & WATER MEASUREMENTS


The Rosemount 8750W offers reliability and advanced process insight in an intuitive, easy-to-use solution specifically designed for utility flow measurement.

This system is ideal for water distribution in any process plant, cooling and heating water, water management, influent and effluent flows, wastewater, and desalination, making it an economical solution for nearly any water- or utility-related application.



Reliability by Design

- ✓ Welded coil housing provides protection against moisture ingress and sustained vibrations
- ✓ Dual compartment transmitter housing keeps the electronics fully isolated from moisture and contamination
- ✓ Replaceable terminal block enables repair in the field
- ✓ Best solution for submersible applications; sensor rated to IP68



Fully welded coil housing



Isolated electronics



WATER

WASTEWATER

UTILITY FLOW



Process Insight

- ✓ SMART™ Meter Verification (SMV) verifies the health of the flowmeter and provides a high level of confidence that readings are accurate
- ✓ Continuous SMV confirms meter calibration without interrupting the process
- ✓ Electrode Coating Diagnostic indicates when preventive maintenance is needed to avoid unexpected downtime
- ✓ Grounding/Wiring Fault Detection recognizes if AC noise is affecting the flow reading
- ✓ Tunable Empty Pipe Detection notifies user if the pipe is not full



“Leveraging the **world-class** smart meter verification and process diagnostics, we significantly **reduced operator rounds** and have more **accurate and reliable reporting** now.”

Utility Manager, Major Chemical Facility



Printable SMV report verifies meter performance for regulatory agencies

Intuitive Solution

- ✓ Available in ProLink® III, enabling easy printing of SMV reports
- ✓ Universal Transmitter capabilities allow easy access to diagnostic information using any manufacture’s sensor
- ✓ Easiest-to-use LOI with dedicated keys for configuration



Specifications

Line Size	0.5" – 48" (15 mm – 1200 mm)
Liner Material	PTFE, Neoprene, Polyurethane
Electrode Material	Stainless Steel, Nickel Alloy
Flange Standard	ANSI, EN, GB, AS4087, AS2129, JIS, AWWA
Flange Rating	Up to 300# / PN40 / 4.0Mpa / PN35 / Table E / 10K / Class F
Accuracy	Standard 0.5%; Optional High Accuracy 0.25%
Mounting	Integral / Remote / Wall Mount
Transmitter Output	4-20mA, Digital HART, Profibus PA, Modbus, Scalable Pulse
Power Supply	AC (90-250 V AC, 50–60 Hz); DC (12–42 V DC)
Hazardous Area Approval	Ordinary Location, FM Class I Div 2, ATEX/IECEx Zone 2, NEPSI Zone 2
Process Diagnostics	Empty Pipe, Grounding/Wiring Detection, Coated Electrode Detection
SMART™ Meter Verification	Meter Integrity
Drinking Water Certification	NSF
Sensor Ingress Protection	IP68

Rosemount 8750W Magnetic Flowmeter



Emerson Process Management

8200 Market Boulevard
Chanhassen, MN 55317, USA
☎ +1 800 999 9307 or +1 952 906 8888
☎ +1 952 949 7001
✉ RMT-NA.RCCRFQ@Emerson.com

Emerson FZE

Emerson FZE P.O. Box 17033,
Jebel Ali Free Zone - South 2
Dubai, United Arab Emirates
☎ T +971 4 8118100
☎ F +971 4 8865465
✉ RFQ.RMTMEA@Emerson.com

Emerson Process Management Flow B.V.

Neonstraat 1
6718 WX Ede
The Netherlands
☎ T +31 (0) 318 495555
☎ F +31 (0) 318 495556

Emerson Process Management Latin America

Multipark Office Center
Turrubares Building, 3rd & 4th floor
Guachipelin de Escazu, Costa Rica
☎ T+(506) 2505-6962
✉ international.mmcam@emersonprocess.com

Emerson Process Management Asia Pacific Pte Ltd

1 Pandan Crescent
Singapore 128461
☎ T +65 6777 8211
☎ F +65 6777 0947
✉ Enquiries@AP.EmersonProcess.com

The Emerson logo is a trademark and service mark of Emerson Electric Co.
Rosemount and the Rosemount logotype are registered trademarks of Rosemount Inc.
All other marks are the property of their respective owners.
© 2016 Emerson Process Management. All rights reserved.

For more information, visit: EmersonProcess.com/Rosemount

ROSEMOUNT™

00803-0100-6162 Rev BA 03/16 / MC-001862


EMERSON™
Process Management

Thị phần số 1 Việt Nam về
**GIẢI PHÁP QUAN TRẮC MÔI TRƯỜNG
& ĐO LƯỜNG CÔNG NGHIỆP**



Trụ sở chính

Số 4E, đường số 6, phường An Phú, Thành Phố Thủ Đức, Thành Phố Hồ Chí Minh.

Hotline: (+84) 901 379 116



Việt An Miền Bắc

Lô 33, khu BT4-1, dự án khu nhà ở Trung Văn, phường Trung Văn, quận Nam Từ Liêm, Hà Nội

Hotline: (+84) 901 851 116



Việt An Miền Trung

Số 5A Mai Xuân Thưởng, phường Hòa Khê, quận Thanh Khê, Thành Phố Đà Nẵng

Hotline: (+84) 898 119 116



Eurowater Technology

Số 9A, đường số 6, phường An Phú, TP. Thủ Đức, TP. Hồ Chí Minh.

Hotline: (+84) 909 788 959

Văn phòng Hà Tĩnh

Tổ dân phố Liên Phú, phường Kỳ Liên, thị xã Kỳ Anh, Hà Tĩnh

Hotline: (+84) 938 442 414